


M400 | SATA | mSATA SSD

SMART Modular's M400 mSATA 2.5" SSDs are designed for demanding enterprise and industrial applications including servers, networking, and storage systems. It supports AES-256 hardware encryption and ATA security features as a Self-Encrypting Drive (SED), and integrates seamlessly into host systems without BIOS or driver modifications.

Built with Single Event Upset (SEU) protection for enhanced data integrity, the M400 helps safeguard against data corruption caused by radiation or voltage fluctuations in harsh environments. It also supports SMART's NVMsentry™ firmware customization services—offering tailored features to meet specific customer requirements in reliability-critical deployments.

3D TLC



Features & Benefits

- 1 DWPD For Five Years
- SEU Mitigation
- SMART's Proprietary NVMSentry Firmware
- Quality of Service (QoS) with 3 Nines of Latency Consistency
- TCG OPAL 2.0 and AES 256 Encryption
- End-to-End Data Path Protection
- Support I-Temp (-40°C to +85°C)

Applications

- Embedded Computing
- Industrial
- Medical
- Transportation

Product Family Overview

Form Factor	Capacity	Sequential Performance
2.5" SSD	240GB to 3840GB	Up to 540MB/s Read Up to 520MB/s Write
M.2 2242 SSD	240GB to 1920GB	
M.2 2280 SSD	240GB to 3840GB	
mSATA SSD	240GB to 3840GB	
Slim SATA SSD	240GB to 3840GB	

Specifications

	M400 | SATA | mSATA SSD
NAND Type	eTLC
Performance	
Host Interface Rate (maximum)	SATA 3.0 6Gb/s
Capacities	240GB to 3840GB
Sequential Read (maximum)	Up to 540 MB/s
Sequential Write (maximum)	Up to 520 MB/s
Random Read (maximum)	Up to 79K IOPS
Random Write (maximum)	Up to 74K IOPS
Reliability	
MTBF	> 2,000,000 hours
Endurance (JEDEC Enterprise Workload)[1]	3840GB: 7100 TBW 1920GB: 4237 TBW 960GB: 2114 TBW 480GB: 920 TBW 240GB: 471 TBW
DWPD	1
SafeDATA	-
Error Correction	LDPC
Data Security	
Encryption	AES-256, TCG OPAL 2.0
Power	
Input Voltage	VCC: 3.3 V ± 5%
Environmental	
Shock	1500 g half-sine, 0.5 msec, 1 shock along each axis, X, Y, Z in each direction
Vibration	20G rms 80-2000Hz, 1.52mm 20-80Hz, 3 axis
Operating Temperature	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
Storage Temperature	-40°C to +85°C
Humidity	40°C, Operation: 90% RH, Storage: 93% RH
Physical	
Length	50.80 mm
Width	29.85 mm
Height	3.95 mm

[1]Endurance is directly related to the User Specific Workload.

Ordering Information

Part Number	Density
M400 | SATA | mSATA SSD Commercial Operating Temperature (0°C to +70°C)	
SRMST3840FCM2AJ1	3840GB
SRMST1920FCM2AJ1	1920GB
SRMST960GFCM2AJ1	960GB
SRMST480GFCM2AJ1	480GB
SRMST240GFCM2AJ1	240GB
M400 | SATA | mSATA SSD Industrial Operating Temperature (-40°C to +85°C)	
SRMST3840FIM2AJ1	3840GB
SRMST1920FIM2AJ1	1920GB
SRMST960GFIM2AJ1	960GB
SRMST480GFIM2AJ1	480GB
SRMST240GFIM2AJ1	240GB

SMART® Modular Technologies
A PENGUIN SOLUTIONS® BRAND

For more information, please visit: **www.smartm.com**

**Product images are for promotional purposes only. Labels may not be representative of the actual product.*

Headquarters/North America:
T: (+1) 800-956-7627 • T: (+1) 510-623-1231
F: (+1) 510-623-1434 • E: info@smartm.com

Latin America:
T: (+55) 11 4417-7200 • E: sales.br@smartm.com

Asia/Pacific:
T: (+65) 6678-7670 • E: sales.asia@smartm.com

EMEA:
T: (+44) 0 7826-064-745 • E: sales.euro@smartm.com

Customer Service:
T: (+1) 510-623-1231 • E: customers@smartm.com

© 2026 SMART Modular Technologies, a Penguin Solutions brand. All rights reserved. The stylized "S" in conjunction with "SMART", as well as "SMART Modular Technologies" are registered trademarks of SMART Modular Technologies. All other trademarks are the property of the respective owners. These materials are provided by SMART Modular Technologies as a service to its customers and may only be used for informational purposes. 03.06.26/M400_mSATA/Rev.1